


Microforet hélice 34° - tige Ø3

342

Mikrobohrer Helix 34° - Schaft Ø3 Micro drill helix 34° - shank Ø3 Micropunta elica 34° - Codolo Ø3

Matière / Material	Vc non rev.	Vc rev.	Rev. recomm. Rec. coating	pas adapté not adapted	adapté adapted	très adapté very adapted
	Vc uncoated	Vc coated				
Acier / Steel < 700 N/mm²	60	70	AlCrN			
Acier / Steel > 700 N/mm²	50	60	AlCrN			
Acier inox / Stainless steel	40	50	AlCrN			
Fonte / Cast iron	30	40	Tin			
Cuivre / Copper	50	60	DLC			
Laiton / Brass - Bronze	120	130	DLC			
Aluminium	130	140	TiAlN			
Or / Gold - Argent / Silver	80	90	DLC			
Platinum - Palladium	-	18	DLC			
Superalloys / Superalloy	-	20	AlCrN			
Titane / Titanium	30	40	TiAlN			

Tolérances
d_i: -0.002/-0.004
D: h5



d _i	l _i	D	L	Prix / Price (CHF)	
				Non revêtu Uncoated	Revêt. std coating
0.10-0.14	0.50	3	38	15.-	21.-
0.15-0.20	0.80	3	38	12.-	18.-
0.21-0.25	1.00	3	38	12.-	18.-
0.26-0.30	1.50	3	38	12.-	18.-
0.31-0.35	2.00	3	38	12.-	18.-
0.36-0.45	3.00	3	38	12.-	18.-
0.46-0.60	4.00	3	38	12.-	18.-
0.61-0.80	5.00	3	38	12.-	18.-
0.81-1.20	6.00	3	38	12.-	18.-
1.21-1.50	8.00	3	38	12.-	18.-
1.51-1.70	8.00	3	38	15.-	21.-
1.71-2.00	12.00	3	38	15.-	21.-

d _i	l _i	D	L	Prix / Price (CHF)	
				Non revêtu Uncoated	Revêt. std coating
2.05	12.00	3	38	18.-	24.-
2.10	12.00	3	38	18.-	24.-
2.15	12.00	3	38	18.-	24.-
2.20	12.00	3	38	18.-	24.-
2.25	12.00	3	38	18.-	24.-
2.30	12.00	3	38	18.-	24.-
2.35	12.00	3	38	18.-	24.-
2.40	12.00	3	38	18.-	24.-
2.45	12.00	3	38	18.-	24.-
2.50	12.00	3	38	18.-	24.-



d_i est disponible tous les centièmes de 0.10 à 2.00 mm
d_i ist in jedem Hundertstel Millimeter von 0.10 bis 2.00 mm verfügbar
d_i available every 0.01 mm from 0.10 to 2.00 mm