

41510

Micro Fraise Hélicoïdale PCD



Matière

Vc

Non revêtu

Acier < 700 N/mm²

-

-

Acier > 700 N/mm²

-

-

Acier inox

-

-

Fonte

-

-

Cuivre

350

■

Laiton - Bronze

500

■

Aluminium

1000

■

Or - Argent

300

■

Platine - Palladium

130

■

Superalliages

-

-

Titane

-

-

Composite

200

□

pas adapté -

adapté □

trèsadapté ■

Brut uniquement
Raw only - Nur rohe
Solo grezzo

Tolérances

D₁ < 1mm : 0/-0.01D₁ > 1mm : 0/-0.02

D: h5



PCD



Z2-3



8-10°



λ 30°

ap=0.15xd₁ae=0.03xd₁
ap=1xd₁

Art. n°	d1	l1	D	L	Z
41510d0.20	0.20	0.20	3	38	2
41510d0.30	0.30	0.30	3	38	2
41510d0.40	0.40	0.40	3	38	2
41510d0.50	0.50	0.50	3	38	3
41510d0.60	0.60	0.60	3	38	3
41510d0.70	0.70	0.70	3	38	3
41510d0.80	0.80	0.80	3	38	3
41510d0.90	0.90	0.90	3	38	3
41510d1.00	1.00	1.00	3	38	3
41510d1.10	1.10	1.10	3	38	3
41510d1.20	1.20	1.20	3	38	3
41510d1.30	1.30	1.30	3	38	3
41510d1.40	1.40	1.40	3	38	3
41510d1.50	1.50	1.50	3	38	3

Options
(voir page 000)

7015
≤ Ø6

MCU
≤ Ø3

Autres dimensions sur demande