



| Matière | Vc non rev. | Vc rev. | Brut | Revêtu | Rev. recomm.* |
|-------------------|-------------|---------|------|--------|---------------|
| Acier 20AP | 70 | 90 | ■ | □ | TRIO (PO) |
| Acier Law 100X | 70 | 90 | ■ | □ | TRIO (PO) |
| Finemac | 50 | 60 | ■ | ■ | TRIO (PO) |
| 4C27A | 60 | 70 | ■ | ■ | TRIO (PO) |
| CK45 | 80 | 90 | ■ | ■ | TRIO (PO) |
| 316L | 60 | 70 | ■ | ■ | TRIO (PO) |
| Autre Inox | 60 | 70 | ■ | ■ | TRIO (PO) |
| Laiton avec plomb | 150 | 170 | ■ | - | SOLO (DA) |
| Laiton sans plomb | 150 | 170 | ■ | □ | SOLO (DA) |
| CuBe | 100 | 120 | ■ | □ | SOLO (DA) |
| Maillechort | 120 | 140 | ■ | □ | SOLO (DA) |
| Bronze | 120 | 140 | ■ | □ | SOLO (DA) |
| Aluminium | 200 | 220 | ■ | - | SOLO (DA) |
| Titane | 80 | 90 | ■ | - | - |

Tolérances d_2 : H3 e : +0/-0.01

Modules standards: 0.015 à 1.000. Autres modules : sur demande

Disponible brut ou revêtu

Z
12-15

λ
0°

γ
0°

CARB

| d_1 | e | d_2 | Z | d_1 | e | d_2 | Z |
|-------|-----|-------|-------|-------|-----|-------|----|
| 6 | 4 | 3.5 | 12 | 12 | 6 | 6.0 | 15 |
| 6 | 5 | 3.5 | 12 | 12 | 8 | 6.0 | 15 |
| 6 | 6 | 3.5 | 12 | 16 | 4 | 8.0 | 15 |
| 8 | 4 | 3.5 | 12/15 | 16 | 6 | 8.0 | 15 |
| 8 | 5 | 3.5 | 12/15 | 16 | 8 | 8.0 | 15 |
| 8 | 6 | 3.5 | 12/15 | 16 | 10 | 8.0 | 15 |
| 8 | 6 | 4.5 | 12/15 | 16 | 12 | 8.0 | 15 |
| 8 | 8 | 4.5 | 12/15 | 18 | 6 | 6.0 | 15 |
| 10 | 4 | 3.5 | 12/15 | 18 | 6 | 8.0 | 15 |
| 10 | 4 | 4.0 | 12/15 | 18 | 8 | 8.0 | 15 |
| 10 | 4 | 4.5 | 12/15 | 18 | 10 | 8.0 | 15 |
| 10 | 5 | 3.5 | 12/15 | 18 | 12 | 8.0 | 15 |
| 10 | 6 | 3.5 | 12/15 | 24 | 4 | 8.0 | 15 |
| 10 | 5 | 4.5 | 12/15 | 24 | 5 | 8.0 | 15 |
| 10 | 6 | 4.5 | 12/15 | 24 | 6 | 8.0 | 15 |
| 12 | 6 | 3.5 | 15 | 24 | 8 | 8.0 | 15 |
| 12 | 5 | 4.5 | 15 | 24 | 10 | 8.0 | 15 |
| 12 | 6 | 4.5 | 15 | 24 | 12 | 8.0 | 15 |
| 12 | 8 | 4.5 | 15 | 24 | 15 | 8.0 | 15 |
| 12 | 10 | 4.5 | 15 | 32 | 15 | 13.0 | 15 |
| 12 | 6 | 5.0 | 15 | | | | |
| 12 | 8 | 5.0 | 15 | | | | |