



Matière	Vc non rev.	Vc rev.	Brut	Revêtu	Rev. recommand.
Acier 20AP	70	90	■	□	TRIO (PO)
Acier Low 100X	70	90	■	□	TRIO (PO)
Acier au carbone (Finemac)	50	60	■	■	TRIO (PO)
4C27A	60	70	■	■	TRIO (PO)
CK45	80	90	■	■	TRIO (PO)
316L	60	70	■	■	TRIO (PO)
Autre Inox	60	70	■	■	TRIO (PO)
Laiton avec plomb	150	170	■	-	SOLO (DA)
Laiton sans plomb	150	170	■	□	SOLO (DA)
CuBe	100	120	■	□	SOLO (DA)
Maillechort	120	140	■	□	SOLO (DA)
Bronze	120	140	■	□	SOLO (DA)
Aluminium	200	220	■	-	SOLO (DA)
Titane	80	90	■	-	-

pas adapté - adapté □ très adapté ■

Tolérances d_2 : H3 e : ±0.01

Modules standards: 0.015 à 0.500. Autres modules : sur demande

d_1	e	d_2
6	4	3.5
6	5	3.5
6	6	3.5
8	4	3.5
8	5	3.5
8	6	3.5
10	4	3.5
10	5	3.5
10	6	3.5
10	5	4.5
10	6	4.5
12	6	4.5
12	8	4.5
12	6	5.0
12	8	5.0
12	6	6.0
12	8	6.0
16	6	8.0
16	8	8.0
16	10	8.0
18	6	6.0
18	6	8.0
18	8	8.0
24	6	8.0
24	8	8.0

Disponible
brut ou revêtu



Topping

λ
0°

γ
0°

CARB

$m \geq$
0.015

Z: selon profil

Non topping en option